CLASSIC K 24

COX STUD WELDING GUN FOR DRAWN ARC STUD WELDING



- Weldable stud range 1/8” – 1”
- Suitable for all Elotop machines
- Adjustable plunge dampener
- Robust Housing
- Suitable for jobsite use

Technical data

Diameter Range with Ferrule	1/8”–1” (3–25mm)
Diameter Range Short Cycle	1/8”–3/8” (3–10mm)
Diameter Range Short Cycle (Shielding Gas)	1/8”–1/2” (3–12mm)
Compensation for stud length variations up to	5/16”
Lift Range	2.5-6mm
Standard support with legs	2 (5/16”)
Input Coil Lifting Voltage	60-90
Welding Cable	6ft 4/0
Length without chuck	6-7/8”
Body Diameter	2-3/8”
Height with handle	8-1/2”
Weight without cables	3.1 lbs

Description

K 24 is a robust stud welding gun design for welding threaded & headed studs with ferrules

High Repeatability

Compensation for stud length variations

Ideal for welding shear connectors

Ideal for thru-deck welding

Adjustable plunge dampener for all diameters of studs

Lifting Ring system with length compensation

Control Cable Plug (4 wire)

COX STUD WELDING

By: KÖCO

24700 WOOD COURT ◦ MACOMB ◦ MI ◦ 48042 586-749-6650 www.cox-industries.com